



The Posiflex DT-208 is a mini sized, fully functional, quiet FanFree POS systems, suitable for all types of applications including retail and hospitality. Although small the DT series are perfectly formed, with the efficiency of a much larger system and the DT series boasts 4 serial ports, 3 USB, 1 LAN, 1 cash drawer port and supports 2.5" 40GB HDD or CF card. With the built-in programmable keyboard and touch or non-touch screen the DT series saves even more space. Built with the metal + plastic housing heat is evenly dissipated to allow the DT series to be utilized in everyday and harsh environments and the built-in UPS functionality ensures your system keep running when others fail.

The DT series offers all these features at an affordable price, with a choice of Windows or DOS support, to make your life easier with a Posiflex system.



Fan-free



CPU



WiFi



UPS



Optional built in magnetic stripe reader (MSR).



CF card slot for optional CF memory card which allows booting from HDD or optional CFcard.

- CPU: AMD LX700.
- Support Microsoft WEPOS, POS Ready, WinCE and DOS environment.
- Compact and rugged metal housing including a storage room for HDD and WiFi module.
- 4 COM ports with DC power support for peripheral devices in any industrial application.
- Optional HDD, WiFi module with external antenna.
- Various I/O ports supported.
- DDR SDRAM memory can extend to 1 GB in 1 DDR SO-DIMM module.
- VGA memory size program by software 16 up to 254 MB.
- Built-in UPS function to support the system from intermittent power failure (battery itself is an option).
- Supports power saving mode.

# Posiflex Fan-Free POS Terminal DT-208/208H



Function	DT-208	DT-208 H
CPU	AMD LX-700	
System Memory	DDR SODIMM socket*1, Max 1G.	
Default Memory Size	256 MB	
Power Supply	12 VDC power adaptor	
Housing	Metal + Plastic Housing	
Programmable KB	40 Keys, Stroke Type	
OS support	WinCE / WEPOS / POS Ready / Linux / DOS	
EMI / Safty Certifications	<ul style="list-style-type: none"> <li>· Whole system is CE, FCC class A approved</li> <li>· Power supply is UL, TUV approved</li> <li>· RoHS</li> <li>· WEEE</li> </ul>	
Dimensions	224 mm (W) x 307~312 mm (D) x 108~256 mm(H) or 8.8" x 12.1"~12.3" x 4.3"~10.1"	
Weight	3.3 kg (7.3 lbs)	
<b>Display</b>		
LCD	8" LCD panel 800x600	
Touch Controller	N/A	PS/2
Touch Sensor	N/A	5 Wire Touch Panel
Tilt Adjustment	15°~90°	
<b>Expansion</b>		
Storage Device	2.5" 40 GB IDE HDD or CF memory card (Option)	
CF card slot	Y (memory card only)	
LAN Port	10 / 100 Mb	
Serial Port	4 x DB9	
UPS Port	Y	
Standard USB Port	3 x	
CR Port	1 x	
Power ON only control	Y	
Extension Slot	Y (Mini PCI Slot for Wi-Fi module)	
<b>Environment</b>		
Operation Condition	0°C ~ +40°C or 32°F~ +104°F	
Storage Condition	-20°C ~ +60°C or -4°F~ +140°F	
<b>Options</b>		
Customer Pole Display	PD-201(1x16 LCDM, RS-232 Only) PD-309(2x20 LCDM, 200mm pole) PD-2605(2x20 VFD, 200mm pole)	
UPS Battery	2.3 AH / 12V Lead Acid battery	
CF Memory Card	Optional	
MSR	Optional	
WiFi	Optional	

\*\* The product information and specifications are subject to change without prior notice.

2009 V.02



Optional WLAN module supports IEEE 802.11 a/b/g and WinCE driver.



Optional customer display for integrated base mounted device PD309/U (2 x 20) LCD pole display.



Optional rear mounted device PD-201 LCD customer display.



**Posiflex Technologies, Inc.**  
6, Wu-Chuan Road, Wu Ku, Taipei, Taiwan, R.O.C.  
Tel: 886 2 2299-1599 Fax: 886 2 2299-1819  
sales@posiflex.com.tw www.posiflex.com

